ACRYLITE®

ACRYLITE®
Film

ACRYLITE® Film 0F011

Product

ACRYLITE® Film 0F011 is a transparent, glossy and high weather resistant acrylic film for outdoor applications.

Due to its superior performance under long term weathering and UV light exposure, ACRYLITE® Film 0F011 does not present color change or yellowing.

Therefore it provides an enhanced protection of plastic substrates from degradation caused by UV wave lengths.

Application

ACRYLITE® Film 0F011 is suitable as top layer for high UV and weathering protection of polymeric substrates, especially for PVC decoration films.

Processing

ACRYLITE® Film 0F011 can be laminated onto polymeric substrates such as films or extruded sheets based on PVC, ABS, ASA and PC by in-line or roll-to-roll heat lamination processes.

ACRYLITE® Film 0F011 can also be embossed with different structures on its surface.

ACRYLITE® Film 0F011 displays a very good printing behavior in a wide variety of printing processes.

Sales range

ACRYLITE® Film 0F011 is delivered in standard rolls of 53 µm thickness, 1380 mm width, and 3050 m length.

Custom-made rolls can be produced under prior commercial agreement.

POLYVANTIS

ACRYLITE®
Film

Technical data			
Properties	**Test method**	**Unit**	**Value**
Optical			
Luminous transmittance (D65/10°)	DIN EN ISO 11664	%	92
UV transmittance (280 – 380 nm)	DIN EN 410	%	< 1
Refractive Index	DIN EN ISO 489	%	1.49
Mechanical			
Tensile yield stress (σ_y)	DIN EN ISO 527-3	MPa	35
Yield strain (ε_y)	DIN EN ISO 527-3	%	6
Nominal strain at break (ε_{tB})	DIN EN ISO 527-3	%	> 50
Thermal			
Glass transition temperature Tg (DSC)	DIN EN ISO 11357	°C	94
Miscellaneous			
Accelerated weathering resistance	DIN EN ISO 4892-2, method A, cycle 1	h	12000 No visible change
Density	DIN EN ISO 1183	g/cm³	1.13
Surface tension	DIN ISO 8296	mN/m	42

Distributed by:

PolymerFilms
A DIVISION OF POLYMERSHAPES

www.polymershapes.com

Film East: Tyngsboro, MA | (978) 926-0021

Film Central: Naperville, IL | (331) 204-0272

Film West: Fresno, CA | (559) 383-3456

Film Canada: Dorval, QC | (514) 442-1048

Film Mexico: Apodaca, MX | +52-81-8369-4688

Semi-finished polymethyl methacrylate (PMMA) products from POLYVANTIS are sold on the European, Asian, African and Australian continents under the registered trademark PLEXIGLAS®, in the Americas under the registered trademark ACRYLITE®, both owned by Röhm GmbH, Darmstadt, or its affiliates. Certified to DIN EN ISO 9001 (Quality) and DIN EN ISO 14001 (Environment)

This information and all further technical advice is based on our present knowledge and experience. Such information or advice, whether given at Buyer's request or not, implies no liability or other legal responsibility on our part, including with regard to existing third-party intellectual property rights. In particular, no warranty, whether expressed or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technical progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products should be used.